GENERAL NOTES: INTAKE PIPE SIZE TABLE (SEE NOTE 8) 1. ALL INTERCONNECTING PIPE AND FITTINGS SHALL BE INSTALLED BY THE CONTRACTOR. PIPE LENGTH UNIT SIZE FOR DISCHARGE PIPE SIZING REFER TO 0 - 200' 201' - 400' D 2. ALL PIPING SHALL BE HARD-DRAWN SEAMLESS TYPE "K" OR "L" COPPER TUBING CONFORMING TO DPX 2 STANDARD PRESSURE DROP TABLES. 1.50" 2.00" ASTM DESIGNATION B-819. - TOTAL PRESSURE DROP SHOULD BE PIPE LENGTH LESS THAN 5 PSIG. 0 - 100' 101' - 400' 3. ALL PIPING SHALL BE INSTALLED IN ACCORDANCE WITH NFPA 99. PIPING LAYOUT SOURCE VALVE DPX 3 1.50" 2.00" IS DIAGRAMMATIC ONLY. FINAL ARRANGEMENT WILL BE SITE SPECIFIC. CONTRACTOR WILL BE PIPE LENGTH TO HOSPITAL RESPONSIBLE FOR FIELD VERIFICATION AND COORDINATING ACTUAL LOCATION WITH ALL OTHER 0 - 150' 151' - 400' TRADES. DPX 5 2.00" 2.50" -MAIN PRESSURE GAUGE HIGH-LOW-PIPE LENGTH 4. CONTRACTOR SHALL VERIFY MOTOR VOLTAGE, PHASE, AND AMP RATINGS BEFORE STARTING PRESSURE SWITCH 76' - 250' | 251' - 400' 0 - 75' ELECTRICAL INSTALLATION; AND MAKE CERTAIN THE VOLTAGE SUPPLIED BY THE HOSPITAL IS DPX 7.5 2.00" 2.50" 3.00" THE SAME. EFFECTIVE PIPE LENGTH FOR ELBOWS 5. THE ROOM REQUIRES DEDICATED MECHANICAL VENTILATION WITH AN ALLOWABLE TEMPERATURE PIPE SIZE (IN) 1.50"NPT 2.00" NPT 2.50" NPT 3.00" NPT VARIANCE OF 40° TO 105°. (FOR HIGHER AMBIENTS, CONSULT FACTORY). EFF. PIPE 3.4 4.9 6.4 7.9 6. ELECTRICAL POWER SHOULD BE SUPPLIED FROM THE EQUIPMENT SYSTEM BRANCH OF THE LENGTH (FT) ESSENTIAL ELECTRICAL SYSTEM (EMERGENCY POWER). -SINGLE POINT POWER WIRING ACCESS 7. EQUIPMENT, INSTALLATION, AND TESTING OF THE MEDICAL AIR SYSTEM SHALL COMPLY WITH NFPA 99, AND ALL STATE AND LOCAL CODES OR ORDINANCES. 8. WHEN DETERMINING THE TOTAL PIPE LENGTH, ADD ALL THE STRAIGHT LENGTHS OF PIPE -ALARM WIRING ACCESS TOGETHER IN ADDITION TO THE NUMBER OF ELBOWS TIMES THE EFFECTIVE PIPE LENGTH FOR THE PIPE SIZE. -ETHERNET WIRING ACCESS (SEE EQUIVALENT PIPE LENGTH TABLE & EXAMPLE CALCULATION IN THE O&M MANUAL) 9. ALLOW 36 INCHES IN FRONT OF CONTROL PANEL FOR MAINTENANCE AND VENTILATION, ALL OTHER SIDES REQUIRE 24 INCHES OF CLEARNACE. -DISCHARGE **CONNECTION** PIPE INTAKE TO OUTSIDE, TURN DOWN AND SCREEN PER NFPA 99. (REFER TO TABLE ABOVE FOR CORRECT PIPE SIZING). NOTE: ALL ACCESSORIES, PIPE, AND -SINGLE POINT DRAIN FITTINGS BEYOND INLET AND CONNECTION CONTRACTOR DISCHARGE PORTS ARE SUPPLIED SHALL PIPE TO FLOOR DRAIN AND INSTALLED BY OTHERS. -HEAVY-DUTY **4-POINT ISOLATION** NO VIBRATION PADS ARE-(SEISMIC OPTIONAL) remain the property of BeaconMedaes and may not be used for other than the purpose for which it is loaned without the expressed written permission from BeaconMedaes Engineering. **NECESSARY AT THIS LOCATION BEACONMEDÆ**S 4107 8511 86 NO FOUNDATION OR INERTIA PAD IS REQUIRED (7.5HP WITH 80 GALLON INST DIA - LL DPX SCROLL AIR SPC 2-7.5Hp NFPA W/ DESC HOP230837 RECEIVER SHOWN) (HOUSEKEEPING PAD IS OPTIONAL) DRYERS Sheet1 of 1 DO NOT SCALE T Form F-007 Rev. 01