



- Notes:
1. DISCHARGE CONNECTION HAS INTEGRATED FLEX HOSE DESIGN.
  2. SYSTEM WEIGHT: 3754 LBS
  3. INDICATES LIFTING POINTS
  4. DENOTES CENTER OF GRAVITY
  5. 

SYSTEM CONNECTIONS	
ID	DESCRIPTION
D	DISCHARGE LOCATION
C	CONDENSATE DRAIN LOCATION

Ø0.75  
BOLTDOWN  
(12 PLACES)

MINIMUM CLEARANCE FOR  
MAINTENANCE AND VENTILATION

ALARM WIRING ACCESS

ETHERNET WIRING ACCESS

ELECTRICAL CONNECTION

AIR RECEIVER  
240 GALLON

DEW POINT  
TRANSDUCER

DISCHARGE  
1-1/4" NPT FEMALE

D26.52

D10.90

INTEGRATED  
LIFTING EYES

SINGLE POINT CONDENSATE  
DRAIN CONNECTION  
1/2" NPT (FEMALE)

C5.63

C18.50

ZERO LOSS  
DRAIN VALVE

LIQUID LEVEL SIGHT GLASS  
W/FLOAT INDICATOR

CONTROL CABINET

INTAKE FILTER  
PER COMPRESSOR

AFTERCOOLER

HEAVY-DUTY  
4-POINT ISOLATION  
(SEISMIC OPTIONAL)

Revised:	Date:	Drawn:	Date:
		SMB	07/23/2019
		This drawing and the information contained therein remain the property of BeaconMedaes and may not be used for other than the purpose for which it is loaned without the expressed written permission from BeaconMedaes Engineering.	
Description:		Part Number:	Scale:
DWG GEN ASM QX SCRL LAB 10HP 10BAR 240G -40		4107 8570 07	NTS
Sheet		Rev:	
1 of 1		HOP190259	00
		DO NOT SCALE THIS DOCUMENT	