



- Notes:
- 1. DISCHARGE CONNECTION HAS INTEGRATED FLEX HOSE DESIGN.
  - 2. SYSTEM WEIGHT: 1143 LBS
  - 3. INDICATES LIFTING POINTS
  - 4. DENOTES CENTER OF GRAVITY

| SYSTEM CONNECTIONS |                           |
|--------------------|---------------------------|
| ID                 | DESCRIPTION               |
| D                  | DISCHARGE LOCATION        |
| C                  | CONDENSATE DRAIN LOCATION |

Ø0.75  
BOLTDOWN  
(4 PLACES)

MINIMUM CLEARANCE FOR  
MAINTENANCE & VENTILATION

ELECTRICAL CONNECTION

AIR RECEIVER  
80 GALLON

LIFELINE DUAL DESICCANT  
AIR DRYERS WITH 441 VALVE

DEW POINT  
TRANSDUCER

DISCHARGE  
3/4" NPT (FEMALE)

INTAKE FILTER  
PER COMPRESSOR

AFTERCOOLER

CONTROL CABINET

LIQUID LEVEL  
SIGHT GLASS  
W/ FLOAT INDICATOR

HEAVY-DUTY  
4 POINT ISOLATION  
(SEISMIC OPTIONAL)

INTEGRATED  
LIFTING EYES

|   |                  |  |                            |
|---|------------------|--|----------------------------|
| Revised: MDB  | Date: 11/21/2019 | Drawn: JDY   | Date: 2/10/2011            |
|   |                  | This drawing and the information contained therein remain the property of BeaconMedaes and may not be used for other than the purpose for which it is loaned without the expressed written permission from BeaconMedaes Engineering. |                            |
| Description:<br>GENERAL ASM - LAB AIR DX<br>SCROLL SPC 3HP 10 BAR W/ DESC<br>DRYERS |                  | Part Number:<br>4107 8527 39   | Scale:<br>D                |
| Sheet 1 of 1  |                  | Rev: 02  | DO NOT SCALE THIS DOCUMENT |