



- Notes:
- 1. DISCHARGE CONNECTION HAS INTEGRATED FLEX HOSE DESIGN.
  - 2. SYSTEM WEIGHT: 1997 LBS
  - 3. INDICATES LIFTING POINTS
  - 4. DENOTES CENTER OF GRAVITY

SYSTEM CONNECTIONS	
ID	DESCRIPTION
D	DISCHARGE LOCATION
C	CONDENSATE DRAIN LOCATION

Ø0.75  
BOLTDOWN  
(8 PLACES)

MINIMUM CLEARANCE FOR  
MAINTENANCE & VENTILATION

ELECTRICAL CONNECTION

LIFELINE DUAL DESICCANT  
AIR DRYERS WITH 441 VALVE

DEW POINT  
TRANSDUCER

DISCHARGE  
1 1/4" NPT (FEMALE)

D35.39

INTEGRATED  
LIFTING EYES

SINGLE POINT CONDENSATE  
DRAIN CONNECTION  
1/2" NPT (FEMALE)

C18.49

C5.93

CONTROL CABINET

ZERO LOSS  
DRAIN VALVE

LIQUID LEVEL  
SIGHT GLASS  
W/ FLOAT INDICATOR

AIR RECEIVER  
120 GALLON

INTAKE FILTER  
PER COMPRESSOR

80.52

32.00

26.29

62.00

26.64

34.20

66.00

AFTERCOOLER

HEAVY-DUTY  
4 POINT ISOLATION  
(SEISMIC OPTIONAL)

Revised: MD	Date: 4/9/2020	Drawn: GE CIA	Date: 3/28/2013
		This drawing and the information contained therein remain the property of BeaconMedaes and may not be used for other than the purpose for which it is loaned without the expressed written permission from BeaconMedaes Engineering.	
Description: GENERAL ASM - LAB AIR TX SCROLL SPC 7.5HP 10BAR 120G W/ DESC DRYER		Part Number: 4107 8544 55	
Sheet 1 of 1		Rev: 03	Scale: D