



- Notes:
1. INLET AND DISCHARGE CONNECTIONS HAVE INTEGRATED FLEX HOSE DESIGN.
  2. SYSTEM WEIGHT: 2705 LBS
  3. INDICATES LIFTING POINTS
  4. DENOTES CENTER OF GRAVITY

SYSTEM CONNECTIONS	
ID	DESCRIPTION
D	DISCHARGE LOCATION
C	CONDENSATE DRAIN LOCATION

Ø0.75  
BOLTDOWN  
(8 PLACES)

MINIMUM CLEARANCE FOR  
MAINTENANCE & VENTILATION

ELECTRICAL CONNECTION

LIFELINE DUAL  
DESICCANT AIR  
DRYERS W/ 441 VALVE

DEW POINT  
TRANSDUCER

DISCHARGE  
1-1/4" NPT (FEMALE)

CO TRANSDUCER

CONTROL CABINET

AIR RECEIVER  
240 GALLON

INTAKE FILTER  
PER COMPRESSOR

AFTERCOOLER

HEAVY-DUTY  
4 POINT ISOLATION  
(SEISMIC OPTIONAL)

Revised: MD	Date: 4/9/2020	Drawn: GECIA	Date: 3/22/2013
		This drawing and the information contained therein remain the property of BeaconMedaes and may not be used for other than the purpose for which it is loaned without the expressed written permission from BeaconMedaes Engineering.	
Description: GENERAL ASM - LAB AIR QX SCROLL SPC 7.5HP 10BAR W/ DESC DRYER		Part Number: 4107 8544 59	Scale: D
Sheet 1 of 1		Rev: 03	DO NOT SCALE THIS DOCUMENT