



Notes:

1. DISCHARGE CONNECTION HAS INTEGRATED FLEX HOSE DESIGN.
2. SYSTEM WEIGHT: 3495 LBS
3.  INDICATES LIFTING POINTS
4.  DENOTES CENTER OF GRAVITY

SYSTEM CONNECTIONS	
ID	DESCRIPTION
D	DISCHARGE LOCATION
C	CONDENSATE DRAIN LOCATION

MINIMUM CLEARANCE FOR
MAINTENANCE & VENTILATION

ELECTRICAL CONNECTION

Ø0.75
BOLTDOWNS
(12 PLACES)

LIFELINE DUAL DESICCANT
AIR DRYERS WITH 441 VALVE

DEW POINT
TRANSDUCER

DISCHARGE
1-1/2" NPT
(FEMALE)

D137.39

INTEGRATED
LIFTING EYES

SINGLE POINT CONDENSATE
DRAIN CONNECTION
1/2" NPT (FEMALE)

C18.49

C5.93

LIQUID LEVEL
SIGHT GLASS
W/FLOAT INDICATOR

ZERO LOSS
DRAIN VALVE

CONTROL CABINET

97.23

AIR RECIEVER
240 GALLON

INTAKE FILTER
PER COMPRESSOR

99.50

32.50

52.81

32.50


27.72

72.00

37.60

AFTER COOLER

HEAVY DUTY
4 POINT ISOLATION
(SEISMIC OPTIONAL)

Revised: MD	Date: 4/9/2020	Drawn: GECIA	Date: 3/29/2013
		This drawing and the information contained therein remain the property of BeaconMedaes and may not be used for other than the purpose for which it is loaned without the expressed written permission from BeaconMedaes Engineering.	
Description: GENERAL ASM - LAB AIR TX SCROLL SPC 15HP 10 BAR 240G W/ DESC DRYER		Part Number: 4107 8544 69 DN: HOP200057 Rev: 03 Sheet 1 of 1 DO NOT SCALE THIS DOCUMENT	