



Notes:

1. DISCHARGE CONNECTION HAS INTEGRATED FLEX HOSE DESIGN.
2. SYSTEM WEIGHT: 3392 LBS
3.  INDICATES LIFTING POINTS
4.  DENOTES CENTER OF GRAVITY

SYSTEM CONNECTIONS	
ID	DESCRIPTION
D	DISCHARGE LOCATION
C	CONDENSATE DRAIN LOCATION

MINIMUM CLEARANCE FOR  
MAINTENANCE & VENTILATION

ELECTRICAL CONNECTION

Ø0.75  
BOLTDOWNS  
(12 PLACES)

LIFELINE DUAL DESICCANT  
AIR DRYERS WITH 441 VALVE

DEW POINT  
TRANSDUCER

DISCHARGE  
1-1/2" NPT  
(FEMALE)

D|37.39

INTEGRATED  
LIFTING EYES

SINGLE POINT CONDENSATE  
DRAIN CONECTION  
1/2" NPT (FEMALE)

CONTROL CABINET

85.23

ZERO LOSS  
DRAIN VALVE


LIQUID LEVEL  
SIGHT GLASS  
W/FLOAT INDICATOR

AIR RECEIVER  
200 GALLON

INTAKE FILTER  
PER COMPRESSOR

AFTER COOLER

HEAVY DUTY  
4 POINT ISOLATION  
(SEISMIC OPTIONAL)

Revised: MD	Date: 4/9/2020	Drawn: GECIA	Date: 3/29/2013
		This drawing and the information contained therein remain the property of BeaconMedaes and may not be used for other than the purpose for which it is loaned without the expressed written permission from BeaconMedaes Engineering.	
Description: GENERAL ASM - LAB AIR TX SCROLL SPC 15HP 10 BAR 200G W/ DESC DRYER		Part Number: 4107 8544 68	
DN: HOP200057		Rev: 03	
Sheet 1 of 1		DO NOT SCALE THIS DOCUMENT	